Listing of Claims:

1. (Currently Amended) A photosensor device ~~, which comprises~~ comprising:

a light-applying fiber to apply an inspection light to a subject to be inspected;

a light-receiving fiber to receive a reflected light from the subject to be inspected;

a laser beam source to emit the inspection light to the light-applying fiber;

a photosensor to receive the reflected light via the light-receiving fiber; and

a casing enclosing the light-applying fiber, the light-receiving fiber, the laser beam source and the photosensor,

wherein the light-applying fiber and the light-receiving fiber are bundled to form a fiber bundle, and an objective optical system is provided at a front end of the fiber bundle.

2. (Currently Amended) The photosensor device according to Claim 1, wherein the photosensor device comprises fiber arrays obtained by disposing plural channels of sensor units in the casing, and wherein each of the sensor ~~unit~~ units as one channel comprises ~~the~~ one said light-applying fiber, one said fiber bundle, ~~the light-receiving fiber which forms a pair with the~~

~~light-applying fiber, the~~ one said laser beam source connected to the light-applying fiber of the fiber bundle, and ~~the~~ one said photosensor connected to the light-receiving fiber of the fiber bundle.

3. (Currently Amended) A disk inspection apparatus for irradiating an inspection light on a surface of a rotating disk and inspecting surface conditions of the disk based on a reflected light, ~~which comprises~~ said disk inspection apparatus comprising:

a turning table for rotating the disk ~~fitted thereon~~;

a photosensor body disposed opposite to the surface of the disk; and

a transfer means for reciprocally transferring the photosensor body in a direction perpendicular to a rotating direction of the disk along the surface of the disk;

wherein the photosensor body comprises a fiber array constructed by arranging sensor units as multi-channels, and

wherein each of the sensor units ~~comprising as one unit,~~ comprises:

a light-applying fiber,

a light-receiving fiber which ~~forms a pair~~ is bundled with the light-applying fiber to form a fiber bundle,

a laser beam source ~~connected~~ to emit the inspection light to the light-applying fiber, ~~and~~

a photosensor to receive the reflected light via ~~connected to~~ the light-receiving fiber, and

an objective optical system provided at a front end of the fiber bundle.

4. (Currently Amended) The disk inspection apparatus according to Claim 3, wherein a plurality of the fiber arrays are arranged in plural lines in ~~such~~ a state such that phases of adjacent fiber arrays are shifted.